



10 Watt DC/DC Converters

FEATURES

- COMMERCIAL, CLASS H and CLASS K SCREENING
- PIN FOR PIN COMPATIBILITY
- 16 – 40 VOLT & 36 – 80 VOLT INPUT RANGES
- OUTPUT VOLTAGES TO INCLUDE: 3.3, 5, 12, 15, ± 5 , ± 12 , ± 15
- FULLY ISOLATED
- SHORT CIRCUIT PROTECTION
- INPUT UNDERVOLTAGE LOCKOUT
- OUTPUT OVERVOLTAGE LIMIT
- INHIBIT FUNCTION & OPTIONAL SYNC



DESCRIPTIONS

The MPT 10 Watt DC/DC converters will provide a new level of performance with-out the high price and long lead times of other class H or class K devices. Utilizing thick film hybrid technology, industry leading manufacturing techniques and DC/DC converter design expertise, MPT can provide a new source for DC/DC converters in the commercial, military, aerospace, and space markets.

In a 1.46" x 1.13" x 0.330", pin for pin compatible, hermetically sealed package, the light weight, MPT, 10 Watt converters will offer industry standard performance up to 10 Watts at efficiencies up to 82% at the standard military temperature range of -55°C to 125°C for class H and K devices.

Singles Electrical Characteristics (25°C Tc, 28 VDC Vin, 100% load):

Parameter	3.3 Vout			5 Vout			12 Vout			15 Vout			Units
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Input Voltage	16	28	40	16	28	40	16	28	40	16	28	40	Volts
Input Ripple Current	-	-	50	-	-	50	-	-	50	-	-	50	mAp-p
Output Voltage	3.27	3.3	3.33	4.95	5	5.05	11.88	12	12.12	14.85	15	15.15	Volts
Output Current	-	-	3000	-	-	2000	-	-	833	-	-	667	mA
Output Power	-	-	10	-	-	10	-	-	10	-	-	10	Watts
Efficiency	-	-	75	-	-	78	-	-	82	-	-	82	%
Line Regulation	-	10	30	-	10	50	-	10	50	-	10	50	mV
Load Regulation	-	10	30	-	10	50	-	10	50	-	10	50	mV
Output Ripple Voltage	-	65	150	-	100	300	-	300	500	-	300	500	mV p-p

DUALS ELECTRICAL CHARACTERISTICS (25°C Tc, 28 VDC Vin, 100% load):

Parameter	±5 Vout			±12 Vout			±15 Vout			Units
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Input Voltage	16	28	40	16	28	40	16	28	40	Volts
Input Ripple Current	-	-	50	-	-	50	-	-	50	mA p-p
+ Output Voltage	4.95	5	5.05	11.88	12	12.12	14.85	15	15.15	Volts
- Output Voltage	4.95	5	5.05	11.88	12	12.12	14.85	15	15.15	Volts
Output Current	-	-	±1000	-	-	±415	-	-	±333	mA
Output Power	-	-	10	-	-	10	-	-	10	Watts
Efficiency	-	-	75	-	-	80	-	-	82	%
Line Regulation	-	10	50	-	10	50	-	10	50	mV
Load Regulation	-	10	50	-	10	50	-	10	50	mV
Output Ripple Voltage	-	100	300	300	500		-	300	500	mV p-p

PINOUT

Pin no.	Single Output	Dual Output
1	Inhibit	Inhibit
2	No Connection	Positive Output
3	Output Common	Output Common
4	Positive Output	Negative Output
5	No Connection	No Connection
6	Case Ground	Case Ground
7	Input Common	Input Common
8	Positive Input	Positive Input

For additional information please contact:

Micro-Precision Technologies, Inc.

12-B Manor Parkway

Salem, NH 03079

Tel. No. 603-893-7600

Fax no. 603-893-9110

Email: sales@micropt.com

Visit our Web Site: <http://www.micropt.com>